



Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 06.01.2023

Revision: 06.01.2023

Version number 7 (replaces version 6)

SECTION 1: Identification of the substance/mixture and of the company/ undertaking

· 1.1 Product identifier

· Trade name: **Anodised Aluminium Polish**

· UFI: UNFW-X97T-P00K-WK23

· 1.2 Relevant identified uses of the substance or mixture and uses advised against

· Sector of Use

SU21 Consumer uses: Private households / general public / consumers

SU22 Professional uses: Public domain (administration, education, entertainment, services, craftsmen)

· Application of the substance / the mixture Polishing agent/ Burnishing compound

· 1.3 Details of the supplier of the safety data sheet

· Manufacturer/Supplier:

Dursol-Fabrik Otto Durst GmbH & Co. KG

Martinstr. 22

42655 SOLINGEN

Germany

Tel.: +49 (0)212 - 2718-0

Fax: +49 (0)212 - 208795

www.autosol.de

· Further information obtainable from:

Department Product Safety

labor@autosol.de

· 1.4 Emergency telephone number:

+49 (0) 212 - 2718-0

Only available during the following office hours: Mo-Fr; 08:00 -16:00 h (MEZ/MESZ)

Languages of the phone service: German & English

SECTION 2: Hazards identification

· 2.1 Classification of the substance or mixture

· Classification according to Regulation (EC) No 1272/2008



Eye Irrit. 2 H319 Causes serious eye irritation.

· 2.2 Label elements

· Labelling according to Regulation (EC) No 1272/2008

The product is classified and labelled according to the GB CLP regulation.

· Hazard pictograms



GHS07

· Signal word Warning

(Contd. on page 2)



Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 06.01.2023

Revision: 06.01.2023

Version number 7 (replaces version 6)

Trade name: Anodised Aluminium Polish

(Contd. of page 1)

Hazard statements

H319 Causes serious eye irritation.

Precautionary statements

P102 Keep out of reach of children.

P264 Wash thoroughly after handling.

P280 Wear eye protection / face protection.

P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

P337+P313 If eye irritation persists: Get medical advice/attention.

Additional information: Keep out of reach of children.**2.3 Other hazards****Results of PBT and vPvB assessment****PBT:** Not applicable.**vPvB:** Not applicable.**SECTION 3: Composition/information on ingredients****3.2 Mixtures****Description:** Mixture of substances listed below with nonhazardous additions.**Dangerous components:**

CAS: 67-63-0 EINECS: 200-661-7 Reg.nr.: 01-2119457558-25-xxxx	propan-2-ol Flam. Liq. 2, H225; Eye Irrit. 2, H319; STOT SE 3, H336	1-<10%
	2-Propylheptanol ethoxylate Eye Dam. 1, H318; Acute Tox. 4, H302 Specific concentration limits: Eye Dam. 1; H318: C ≥ 10 % Eye Irrit. 2; H319: 3 % ≤ C < 10 %	1-<10%
CAS: 166736-08-9	Oxiran, 2-Methyl-, Polymer mit Oxiran, mono(2-Propylheptyl) ether Eye Dam. 1, H318; Acute Tox. 4, H302	1-<10%
CAS: 8006-64-2 EINECS: 232-350-7	Turpentine, oil Flam. Liq. 3, H226; Asp. Tox. 1, H304; Aquatic Chronic 2, H411; Acute Tox. 4, H302; Acute Tox. 4, H312; Acute Tox. 4, H332; Skin Irrit. 2, H315; Eye Irrit. 2, H319; Skin Sens. 1, H317	≤1%

Regulation (EC) No 648/2004 on detergents / Labelling for contents

non-ionic surfactants, soap, polycarboxylates

<5%

Additional information: For the wording of the listed hazard phrases refer to section 16.**SECTION 4: First aid measures****4.1 Description of first aid measures****After inhalation:** Supply fresh air; consult doctor in case of complaints.**After skin contact:** Generally the product does not irritate the skin.

(Contd. on page 3)



Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 06.01.2023

Revision: 06.01.2023

Version number 7 (replaces version 6)

Trade name: Anodised Aluminium Polish

(Contd. of page 2)

- **After eye contact:**
Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.
 - **After swallowing:** If symptoms persist consult doctor.
 - **4.2 Most important symptoms and effects, both acute and delayed**
No further relevant information available.
 - **4.3 Indication of any immediate medical attention and special treatment needed**
No further relevant information available.
-

SECTION 5: Firefighting measures

- **5.1 Extinguishing media**
 - **Suitable extinguishing agents:**
CO₂, powder or water spray. Fight larger fires with water spray or alcohol resistant foam.
 - **For safety reasons unsuitable extinguishing agents:** Water with full jet
 - **5.2 Special hazards arising from the substance or mixture** No further relevant information available.
 - **5.3 Advice for firefighters**
 - **Protective equipment:** No special measures required.
 - **Additional information** Cool endangered receptacles with water spray.
-

SECTION 6: Accidental release measures

- **6.1 Personal precautions, protective equipment and emergency procedures** Not required.
 - **6.2 Environmental precautions:** Do not allow to enter sewers/ surface or ground water.
 - **6.3 Methods and material for containment and cleaning up:**
Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).
 - **6.4 Reference to other sections**
See Section 7 for information on safe handling.
See Section 8 for information on personal protection equipment.
See Section 13 for disposal information.
-

SECTION 7: Handling and storage

- **7.1 Precautions for safe handling** No special precautions are necessary if used correctly.
 - **Information about fire - and explosion protection:** No special measures required.
 - **7.2 Conditions for safe storage, including any incompatibilities**
 - **Storage:**
 - **Requirements to be met by storerooms and receptacles:** No special requirements.
 - **Information about storage in one common storage facility:** Not required.
 - **Further information about storage conditions:** Keep container tightly sealed.
 - **Storage class:** 10
 - **7.3 Specific end use(s)** No further relevant information available.
-



Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 06.01.2023

Revision: 06.01.2023

Version number 7 (replaces version 6)

Trade name: Anodised Aluminium Polish

(Contd. of page 3)

SECTION 8: Exposure controls/personal protection

- **8.1 Control parameters**
- **Ingredients with limit values that require monitoring at the workplace:**
The product does not contain any relevant quantities of materials with critical values that have to be monitored at the workplace.
- **Additional information:** The lists valid during the making were used as basis.

- **8.2 Exposure controls**

- **Appropriate engineering controls** No further data; see item 7.
- **Individual protection measures, such as personal protective equipment**
- **General protective and hygienic measures:**
The usual precautionary measures are to be adhered to when handling chemicals.
Keep away from foodstuffs, beverages and feed.
Immediately remove all soiled and contaminated clothing
Wash hands before breaks and at the end of work.
Avoid contact with the eyes.
Avoid contact with the eyes and skin.

- **Respiratory protection:**

Filter A/P2
In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use self-contained respiratory protective device.

- **Hand protection**



Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation. Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

- **Material of gloves**

Nitrile rubber, NBR

Recommended thickness of the material: ≥ 0.5 mm

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

- **Penetration time of glove material**

For the mixture of chemicals mentioned below the penetration time has to be at least 480 minutes

(Permeation according to EN 16523-1:2015: Level 6).

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

(Contd. on page 5)

— GB —



Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 06.01.2023

Revision: 06.01.2023

Version number 7 (replaces version 6)

Trade name: Anodised Aluminium Polish

(Contd. of page 4)

· Eye/face protection

Tightly sealed goggles

SECTION 9: Physical and chemical properties**· 9.1 Information on basic physical and chemical properties****· General Information**

· Colour:	Beige
· Odour:	Characteristic
· Odour threshold:	Not determined.
· Melting point/freezing point:	Undetermined.
· Boiling point or initial boiling point and boiling range	100 °C
· Flammability	Not applicable.
· Lower and upper explosion limit	
· Lower:	Not determined.
· Upper:	Not determined.
· Flash point:	49 °C (No Combustibility)
· Decomposition temperature:	Not determined.
· pH at 20 °C	6
· Viscosity:	
· Kinematic viscosity	Not determined.
· Dynamic:	Not determined.
· Solubility	
· water:	Not miscible or difficult to mix.
· Partition coefficient n-octanol/water (log value)	Not determined.
· Vapour pressure:	Not determined.
· Density and/or relative density	
· Density at 20 °C:	0.98 g/cm ³
· Relative density	Not determined.
· Vapour density	Not determined.

· 9.2 Other information

· Appearance:	
· Form:	Pasty
· Important information on protection of health and environment, and on safety.	
· Auto-ignition temperature:	Product is not selfigniting.
· Explosive properties:	Product does not present an explosion hazard.
· Change in condition	
· Evaporation rate	Not determined.

(Contd. on page 6)

— GB —



Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 06.01.2023

Revision: 06.01.2023

Version number 7 (replaces version 6)

Trade name: Anodised Aluminium Polish

(Contd. of page 5)

· Information with regard to physical hazard classes	
· Explosives	Void
· Flammable gases	Void
· Aerosols	Void
· Oxidising gases	Void
· Gases under pressure	Void
· Flammable liquids	Void
· Flammable solids	Void
· Self-reactive substances and mixtures	Void
· Pyrophoric liquids	Void
· Pyrophoric solids	Void
· Self-heating substances and mixtures	Void
· Substances and mixtures, which emit flammable gases in contact with water	Void
· Oxidising liquids	Void
· Oxidising solids	Void
· Organic peroxides	Void
· Corrosive to metals	Void
· Desensitised explosives	Void

SECTION 10: Stability and reactivity

- **10.1 Reactivity** No further relevant information available.
- **10.2 Chemical stability**
- **Thermal decomposition / conditions to be avoided:**
No decomposition if used according to specifications.
- **10.3 Possibility of hazardous reactions** No dangerous reactions known.
- **10.4 Conditions to avoid** No further relevant information available.
- **10.5 Incompatible materials:** No further relevant information available.
- **10.6 Hazardous decomposition products:** No dangerous decomposition products known.

SECTION 11: Toxicological information

- **11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008**
- **Acute toxicity** Based on available data, the classification criteria are not met.

· LD/LC50 values relevant for classification:

67-63-0 propan-2-ol

Oral	LD50	5045 mg/kg (rat)
Dermal	LD50	12800 mg/kg (rabbit)
Inhalative	LC50 (4 h)	30 mg/l (rat)

2-Propylheptanol ethoxylate

Oral	LD50	700-1700, mg/kg (rat)
------	------	-----------------------

(Contd. on page 7)



Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 06.01.2023

Revision: 06.01.2023

Version number 7 (replaces version 6)

Trade name: Anodised Aluminium Polish

(Contd. of page 6)

166736-08-9 Oxiran, 2-Methyl-, Polymer mit Oxiran, mono(2-Propylheptyl) ether

Oral	LD50	500 mg/kg (rat)
------	------	-----------------

- **Skin corrosion/irritation** Based on available data, the classification criteria are not met.
- **Serious eye damage/irritation**
Causes serious eye irritation.
- **Respiratory or skin sensitisation** Based on available data, the classification criteria are not met.
- **Germ cell mutagenicity** Based on available data, the classification criteria are not met.
- **Carcinogenicity** Based on available data, the classification criteria are not met.
- **Reproductive toxicity** Based on available data, the classification criteria are not met.
- **STOT-single exposure** Based on available data, the classification criteria are not met.
- **STOT-repeated exposure** Based on available data, the classification criteria are not met.
- **Aspiration hazard** Based on available data, the classification criteria are not met.
- **11.2 Information on other hazards**

Endocrine disrupting properties

None of the ingredients is listed.

SECTION 12: Ecological information**12.1 Toxicity****Aquatic toxicity:****67-63-0 propan-2-ol**

LC50 (96 h) > 100 mg/l (fish)

LC50 > 100 mg/l (daphnia)

166736-08-9 Oxiran, 2-Methyl-, Polymer mit Oxiran, mono(2-Propylheptyl) ether

LC50 (96 h) 10-100 mg/l (fish)

LC50 (48 h) 1-10 mg/l (daphnia)

- **12.2 Persistence and degradability** No further relevant information available.
- **12.3 Bioaccumulative potential** No further relevant information available.
- **12.4 Mobility in soil** No further relevant information available.
- **12.5 Results of PBT and vPvB assessment**
 - **PBT:** Not applicable.
 - **vPvB:** Not applicable.
- **12.6 Endocrine disrupting properties** For information on endocrine disrupting properties see section 11.
- **12.7 Other adverse effects**
- **Additional ecological information:**
- **General notes:**
Water hazard class 2 (German Regulation) (Self-assessment): hazardous for water
Do not allow product to reach ground water, water course or sewage system.
Danger to drinking water if even small quantities leak into the ground.

GB —

(Contd. on page 8)



Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 06.01.2023

Revision: 06.01.2023

Version number 7 (replaces version 6)

Trade name: Anodised Aluminium Polish

(Contd. of page 7)

SECTION 13: Disposal considerations

· 13.1 Waste treatment methods

· Recommendation

Must not be disposed together with household garbage. Do not allow product to reach sewage system.

· Uncleaned packaging:

· Recommendation: Disposal must be made according to official regulations.

SECTION 14: Transport information

· 14.1 UN number or ID number · ADR, ADN, IMDG, IATA	Void
· 14.2 UN proper shipping name · ADR, ADN, IMDG, IATA	Void
· 14.3 Transport hazard class(es) · ADR, ADN, IMDG, IATA · Class	Void
· 14.4 Packing group · ADR, IMDG, IATA	Void
· 14.5 Environmental hazards: · Marine pollutant:	No
· 14.6 Special precautions for user	Not applicable.
· 14.7 Maritime transport in bulk according to IMO instruments	Not applicable.
· UN "Model Regulation":	Void

SECTION 15: Regulatory information

· 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

· Directive 2012/18/EU

· Named dangerous substances - ANNEX I None of the ingredients is listed.

· 15.2 Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

SECTION 16: Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

· Relevant phrases

H225 Highly flammable liquid and vapour.

H226 Flammable liquid and vapour.

(Contd. on page 9)

— GB —



Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 06.01.2023

Revision: 06.01.2023

Version number 7 (replaces version 6)

Trade name: Anodised Aluminium Polish

(Contd. of page 8)

H302 Harmful if swallowed.
H304 May be fatal if swallowed and enters airways.
H312 Harmful in contact with skin.
H315 Causes skin irritation.
H317 May cause an allergic skin reaction.
H318 Causes serious eye damage.
H319 Causes serious eye irritation.
H332 Harmful if inhaled.
H336 May cause drowsiness or dizziness.
H411 Toxic to aquatic life with long lasting effects.

· **Department issuing SDS:**

Dursol-Fabrik Otto Durst GmbH & Co. KG
Martinstraße 22
42655 Solingen
Germany

Abteilung F&E / Produktsicherheit

· **Contact:** labor@autosol.de

· **Abbreviations and acronyms:**

ADR: Accord relatif au transport international des marchandises dangereuses par route (European Agreement Concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association

GHS: Globally Harmonised System of Classification and Labelling of Chemicals

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

PBT: Persistent, Bioaccumulative and Toxic

vPvB: very Persistent and very Bioaccumulative

Flam. Liq. 2: Flammable liquids – Category 2

Flam. Liq. 3: Flammable liquids – Category 3

Acute Tox. 4: Acute toxicity – Category 4

Skin Irrit. 2: Skin corrosion/irritation – Category 2

Eye Dam. 1: Serious eye damage/eye irritation – Category 1

Eye Irrit. 2: Serious eye damage/eye irritation – Category 2

Skin Sens. 1: Skin sensitisation – Category 1

STOT SE 3: Specific target organ toxicity (single exposure) – Category 3

Asp. Tox. 1: Aspiration hazard – Category 1

Aquatic Chronic 2: Hazardous to the aquatic environment - long-term aquatic hazard – Category 2

· *** Data compared to the previous version altered.**