

# Granville Platinum Plus 10W/40

1 Litre, 5 Litre & 20 Litre

## PRODUCT DESCRIPTION

Granville Platinum Plus 10W/40 is a high performance semi synthetic oil suitable for petrol and diesel engines including turbo, fuel injection and those fitted with catalytic converters.

## RECOMMENDED FOR USE BY GRANVILLE FOR THE FOLLOWING MANUFACTURER'S SPECIFICATIONS

VW: 502.00 & 505.00

ACEA: A3/B4

API: SN/CF

MB: 229.3

Renault: RN0700 & RN0710



\* Image for illustrative purposes only.

## PRODUCT BENEFITS

- \* Ensures lubricant performance
- \* Excellent high & low temperature performance
- \* Outstanding fuel efficiency
- \* Effective environmental protection

| SIZE     | PART NO | BARCODE       |
|----------|---------|---------------|
| 1 Litre  | 0045    | 5020618000457 |
| 5 Litre  | 0043    | 5020618000433 |
| 20 Litre | 0295    | 5020618002956 |

## PRODUCT USAGE

For engines where this specification of lubricant is required

## DIRECTIONS FOR USE

As recommended by the engine manufacturer

## STORAGE INSTRUCTIONS

Keep upright and sealed in a cool, dry place out of the reach of children



# Granville Platinum Plus 10W/40

1 Litre, 5 Litre & 20 Litre

## SHELF LIFE

5 years from date of manufacture

|                         |                      |
|-------------------------|----------------------|
| Appearance              | : Amber liquid       |
| Odour                   | : Characteristic     |
| Solubility              | : Insoluble in water |
| Percentage of Base Oil  | : Less than 70%      |
| Percentage of Biodiesel | : Nil                |

| Test                       | Method     | Unit               | Min. | Max.  | Typical |
|----------------------------|------------|--------------------|------|-------|---------|
| Viscosity, Kinematic 100°C | ASTM D445  | mm <sup>2</sup> /s | 12.5 | <16.3 | 13.46   |
| Viscosity, CCS -25°C       | ASTM D4684 | mPa.s              |      | 7000  |         |
| Total Base Number          | ASTM D2896 | mg KOH/g           | 10   |       | 11.25   |
| Pour Point                 | ASTM D97   | °C                 |      | -35   | -33     |
| HTHS Viscosity             | ASTM D4683 | mPa.s              | 3.5  |       |         |
| NOACK Volatility           | ASTM D5800 | %                  |      | 12    |         |
| Viscosity, Kinematic 40°C  | ASTM D445  | mm <sup>2</sup> /s |      |       | 81.77   |
| Density                    | ASTM D792  | @ 15°C             |      |       | 0.872   |
| Viscosity Index            | ASTM D2270 |                    |      |       | 160.96  |

## SAFETY PRECAUTIONS

Please see our latest EC Safety Data Sheets for details.

## TRANSPORT CLASSIFICATION

Please see our latest EC Safety Data Sheets for details.

