

Granville Diesel Gold 15W/40

5 Litre

PRODUCT DESCRIPTION

Granville Diesel Gold 15W/40 is a semi-synthetic engine oil for use in older engines requiring a lubricant of this grade.

RECOMMENDED FOR USE BY GRANVILLE FOR THE FOLLOWING MANUFACTURER'S SPECIFICATIONS

VW: 505.00 & 502.00
ACEA: A3/B4
API: SN/CF
MB: 229.3

PRODUCT BENEFITS

- * Ensures lubricant performance
- * Excellent high & low temperature performance
- * Outstanding fuel efficiency
- * Effective environmental protection

PRODUCT USAGE

For engines where this specification lubricant is required.

DIRECTIONS FOR USE

As recommended by the engine manufacturer.

STORAGE INSTRUCTIONS

Keep sealed in a cool, dry place.

SHELF LIFE

5 years from date of manufacture.

Appearance : Amber liquid



* Image for illustrative purposes only.

SIZE	PART NO	BARCODE
5 Litre	0880	5020618008804



Granville Diesel Gold 15W/40

5 Litre

Odour : Characteristic

Solubility : Insoluble

Test	Method	Unit	Min.	Max.	Typical
Viscosity, Kinematic 100°C	ASTM D445	mm ² /s	12.5	<16.3	
Viscosity Index	ASTM D2270		80		
Viscosity, CCS -20°C	ASTM D4684	mPa.s		7000	
Total Base Number	ASTM D2896	mg KOH/g	10		
Pour Point	ASTM D97	°C		-27	
HTHS Viscosity	ASTM D4683	mPa.s	3.7		
NOACK Volatility	ASTM D5800	%		13	

SAFETY PRECAUTIONS

Please see our latest EC Safety Data Sheets for details.

TRANSPORT CLASSIFICATION

Please see our latest EC Safety Data Sheets for details.

