

## TECHNICAL DATA

# Granville Hypalube 30 Mineral

1 Litre, 5 Litre, 20 Litre & 199 Litre

#### PRODUCT DESCRIPTION

Granville Hypalube SAE 30 motor oil is a monograde engine oil formulated for vintage and classic 4 stroke petrol engines, plant and garden machinery where SAE 30 lubricant is recommended.

### RECOMMENDED FOR USE BY GRANVILLE FOR THE FOLLOWING MANUFACTURER'S SPECIFICATIONS

API: SF/CC SAE: 30

#### PRODUCT BENEFITS

- \* Monograde SAE 30 engine oil
- \* Excellent high & low temperature performance

#### PRODUCT USAGE

For engines where this specification lubricant is required.

#### **DIRECTIONS FOR USE**

As recommended by the engine manufacturer.

#### STORAGE INSTRUCTIONS

Keep sealed in a cool, dry place.

#### **SHELF LIFE**

 ${\bf 5}$  years from date of manufacture.

Revision: 3 | Date: 17/07/2023

**Appearance** : Amber liquid



\* Image for illustrative purposes only.

SIZE	PART NO	BARCODE
1 Litre	1819	5020618018193
5 Litre	1802	5020618018025
20 Litre	1832	5020618018322
199 Litre	1820	5020618018209





### TECHNICAL DATA

# Granville Hypalube 30 Mineral

1 Litre, 5 Litre, 20 Litre & 199 Litre

Odour: CharacteristicSolubility: Insoluble in water

Test	Method	Unit	Min.	Max.	Typical
Viscosity, Kinematic 100°c	ASTM D445	mm²/s	9.3	<12.5	10.57
HTHS Viscosity	ASTM D4683	mPa.s	2.9		
Viscosity, Kinematic 40°c	ASTM D445	mm²/s			89.87
Density	ASTM D792	@ 15°c			0.876
Total Base Number	ASTM D2896	mg KOH/g			6.22
Viscosity Index	ASTM D2270		75		
Pour Point	ASTM D97	°c		-15	

#### **SAFETY PRECAUTIONS**

Revision: 3 | Date: 17/07/2023

Please see our latest EC Safety Data Sheets for details.

#### TRANSPORT CLASSIFICATION

Please see our latest EC Safety Data Sheets for details.

