

Granville ATF Dexron III

1 Litre, 5 Litre, 20 Litre & 205 Litre

PRODUCT DESCRIPTION

Granville ATF Dexron III is a synthetic based multi-purpose automatic transmission fluid for automatic gearboxes. ATF Dexron III is formulated using the very latest additive technology to give a product that is frictionally stable as well as giving extended service even under the most testing of conditions.

RECOMMENDED FOR USE BY GRANVILLE FOR THE FOLLOWING MANUFACTURER'S SPECIFICATIONS

GM: Dexron II & Dexron III

Ford: WSS-M2C138-J & WSS-M2C166-H

Allison: C4

MB: 236.5 & 236.9

ZF: TE-ML-09, TE-ML-11 & TE-ML-14



* Image for illustrative purposes only.

PRODUCT BENEFITS

- * Semi synthetic
- * Extended service life
- * Excellent protection & stability

PRODUCT USAGE

Granville ATF Dexron III is designed for use in automatic transmissions manufactured by General Motors, Vauxhall and Opel to name but a few. It may also be used in other manufacturer's vehicles where recommended and as a power steering fluid where recommended.

DIRECTIONS FOR USE

As recommended by the vehicle manufacturer.

SIZE	PART NO	BARCODE
1 Litre	0224	5020618002246
5 Litre	0225	5020618002253
20 Litre	0090	5020618000907
205 Litre	0229	5020618002291



Granville ATF Dexron III

1 Litre, 5 Litre, 20 Litre & 205 Litre

STORAGE INSTRUCTIONS

Store sealed in a cool, dry place

SHELF LIFE

5 years from date of manufacture.

Appearance	: Red liquid
Odour	: Characteristic
Solubility	: Insoluble in water
Percentage of Base Oil	: Less than 70%
Percentage of Biodiesel	: Nil

Test	Method	Unit	Min.	Max.	Typical
Viscosity, Kinematic 100°C	ASTM D445	mm ² /s			7.55
Viscosity, Kinematic 40°C	ASTM D445	mm ² /s			37.26
Density	ASTM D792	@ 15°C			0.848

SAFETY PRECAUTIONS

Please see our latest EC Safety Data Sheets for details.

TRANSPORT CLASSIFICATION

Please see our latest EC Safety Data Sheets for details.

