

Granville DCT Fluid

1 Litre, 5 Litre & 205 Litre

PRODUCT DESCRIPTION

Granville DCT fluid is an advanced fully synthetic Dual Clutch transmission fluid suitable for use in certain vehicles fitted with DSG or DCT wet transmission. Specially formulated to control heat and wear within the transmission offering extended component durability and protection.

RECOMMENDED FOR USE BY GRANVILLE FOR THE FOLLOWING MANUFACTURER'S SPECIFICATIONS

VW: G 052 182, G 052 529 (2003-) & G 055 529

PSA: 9734.S2

Ford: M2C936-A & M2C218-A1

Mitsubishi: Dia Queen SSTF-1 (2007-)

BMW: DCTF-1, DCT (6 Speed), MTF LT-5 & DCTF-2

MB: 236.21

Volvo: 1161838 & 1161839

Castrol: BOT 341, BOT 450 & Transmax Dual

Pentosin: Pentosin FFL 2, Pentosin FFL 3, Pentosin FFL 4 & Pentosin FFL 52529

Porsche: 999.917.080.00

Renault: EDC-6 speed (Getrag), EDC-7 speed (Getrag) & DW5

Ferrari: 7 speed (Getrag) TF DCT-3

Shell: TF DCT-F3



* Image for illustrative purposes only.

SIZE	PART NO	BARCODE
1 Litre	1573	5020618015734
5 Litre	1574	5020618015741
205 Litre	1576	5020618015765

PRODUCT BENEFITS

- * Excellent temperature control
- * Protect components extending service life
- * Fully synthetic formulation

PRODUCT USAGE

Suitable for use in certain vehicles fitted with DSG or DCT wet transmissions.



Granville DCT Fluid

1 Litre, 5 Litre & 205 Litre

DIRECTIONS FOR USE

Use as per manufacturers recommendations

STORAGE INSTRUCTIONS

Store sealed in a cool, dry place out of the reach of children

SHELF LIFE

5 years from date of manufacture

Appearance : Clear Amber Liquid

Odour : Characteristic

Test	Method	Unit	Min.	Max.	Typical
Density	ASTM D792	@ 15°C			0.846
Viscosity, Kinematic 100°C	ASTM D445	mm ² /s	6.5	8.5	7.73

SAFETY PRECAUTIONS

Please see our latest EC Safety Data Sheets for details.

TRANSPORT CLASSIFICATION

Please see our latest EC Safety Data Sheets for details.

