

TECHNICAL DATA

Granville Hy-Vis Hydraulic 100

20 Litre & 199 Litre

PRODUCT DESCRIPTION

Hypalube Hy-vis 100 hydraulic oil is formulated for use in a wide range of agricultural, commercial and industrial applications, it offers excellent pumpability and protects against oxidation and corrosion.

RECOMMENDED FOR USE BY GRANVILLE FOR THE FOLLOWING MANUFACTURER'S SPECIFICATIONS

AFNOR: NF E 48603 David Brown: S1.53.101

Denison Filterability: TP02100 DIN: 51524 Part 2 (HLP) Vickers: 1.286.S & 1.286.S3

PRODUCT BENEFITS

*Excellent pumpability

*Protects against oxidation and corrosion.

CONNECTION AND CONTROL LABORATOR AND CONTROL

* Image for illustrative purposes only.

| SIZE | PART NO | BARCODE |
|-----------|---------|---------------|
| 20 Litre | 0726 | 5020618007265 |
| 199 Litre | 179B | 5020618023395 |

STORAGE INSTRUCTIONS

Store upright and sealed in a cool place and out of the reach of children

SHELF LIFE

5 years from date of manufacture

Revision: 1 | Date: 17/01/2023

Appearance : Amber liquid





TECHNICAL DATA

Granville Hy-Vis Hydraulic 100

20 Litre & 199 Litre

Odour : Characteristic

Solubility : Insoluble in water

Percentage of Biodiesel : Nil

| Test | Method | Unit | Min. | Max. | Typical |
|----------------------------|-----------|--------|------|------|---------|
| Viscosity, Kinematic 40°c | ASTM D445 | mm²/s | 90 | 110 | 92.54 |
| Viscosity, Kinematic 100°c | ASTM D445 | mm²/s | | | 10.64 |
| Density | ASTM D792 | @ 15°c | | | 0.881 |

SAFETY PRECAUTIONS

Revision: 1 | Date: 17/01/2023

Please see our latest EC Safety Data Sheets for details.

TRANSPORT CLASSIFICATION

Please see our latest EC Safety Data Sheets for details.

