

## Granville Hypafarm SUTO 10W/30

20 Litre & 199 Litre

### PRODUCT DESCRIPTION

Hypafarm SUTO 10W/30 is a multi-functional agricultural oil formulated using quality additives and base oils to enable this product to be used in petrol and diesel engines both naturally aspirated and turbo charged as well as transmissions, final drive, hydraulic and oil immersed brake applications.

### RECOMMENDED FOR USE BY GRANVILLE FOR THE FOLLOWING MANUFACTURER'S SPECIFICATIONS

API: CG-4/SF & GL-4

MB: 227.1 & 228.1

Ford: WSS-M2C159B, WSS-M2C159C, WSS-M2C134-D, WSS-M2C86-A & WSS-M2C86-B

John Deere: JDM 20A

Massey Ferguson: M1135, M1139, M1144 & M1145

New Holland: 82009201, 024C & 030C

Allison: C4

Case: MS1206

CAT: TO-2

ZF: TE-ML-03A, TE-ML-06A, TE-ML-07D, TE-ML-06B, TE-ML-06C & TE-ML-07B



\* Image for illustrative purposes only.

| SIZE      | PART NO | BARCODE       |
|-----------|---------|---------------|
| 20 Litre  | 6507    | 5020618065074 |
| 199 Litre | 6509    | 5020618065098 |

### PRODUCT BENEFITS

\*Suitable for Petrol and Diesel Engines

\*Specially selected additive for greater protection

### PRODUCT USAGE

For use where this type and viscosity oil is required

### DIRECTIONS FOR USE

Use as per the component manufacturers recommendations



# Granville Hypafarm SUTO 10W/30

20 Litre & 199 Litre

## STORAGE INSTRUCTIONS

Store upright and sealed in a cool place and keep out of the reach of children

## SHELF LIFE

5 years from date of manufacture

|                         |                      |
|-------------------------|----------------------|
| Appearance              | : Amber liquid       |
| Odour                   | : Characteristic     |
| Solubility              | : Insoluble in water |
| Percentage of Biodiesel | : Nil                |

| Test                       | Method     | Unit               | Min. | Max. | Typical |
|----------------------------|------------|--------------------|------|------|---------|
| Viscosity, Kinematic 100°C | ASTM D445  | mm <sup>2</sup> /s | 9.3  | 12.5 |         |
| Viscosity, CCS -25°C       | ASTM D4684 | mPa.s              |      | 7000 |         |
| Pour Point                 | ASTM D97   | °C                 |      | -30  |         |
| HTHS Viscosity             | ASTM D4683 | mPa.s              | 2.9  |      |         |

## SAFETY PRECAUTIONS

Please see our latest EC Safety Data Sheets for details.

## TRANSPORT CLASSIFICATION

Please see our latest EC Safety Data Sheets for details.

