

Granville Hypalube DX FS 0W/20

1 Litre, 5 Litre, 20 Litre & 199 Litre

PRODUCT DESCRIPTION

Granville Hypalube DX 0W/20 is an advanced fully synthetic low viscosity engine oil formulated for fuel efficiency. It provides excellent wear protection under the most extreme circumstances even at cold start up. This viscosity of oil may not be suitable for use in certain engine types, please refer to the owner manual or handbook.

RECOMMENDED FOR USE BY GRANVILLE FOR THE FOLLOWING MANUFACTURER'S SPECIFICATIONS

API: SN, SN-RC & SP

Chrysler: MS 6395

GM: 4718M, 6094M, Dexos™ 1 Gen 2 & Dexos™ 1 Gen 3

ILSAC: GF-5 & GF-6A



* Image for illustrative purposes only.

PRODUCT BENEFITS

*Fully synthetic low viscosity fuel efficient engine oil

*Ideal for petrol and hybrid engines

PRODUCT USAGE

For engines where this specification lubricant is required.

DIRECTIONS FOR USE

As recommended by the engine manufacturer.

STORAGE INSTRUCTIONS

Keep sealed in a cool, dry place.

SHELF LIFE

5 years from date of manufacture.

Appearance : Amber liquid

SIZE	PART NO	BARCODE
1 Litre	1164	5020618011644
5 Litre	1165	5020618011651
20 Litre	1166	5020618011668
199 Litre	1168	5020618011682



Granville Hypalube DX FS 0W/20

1 Litre, 5 Litre, 20 Litre & 199 Litre

Odour : Characteristic
Solubility : Insoluble in water

Test	Method	Unit	Min.	Max.	Typical
Viscosity, Kinematic 100°C	ASTM D445	mm ² /s	6.9	9.3	8.5
Viscosity, CCS -35°C	ASTM D4684	mPa.s		6200	
Total Base Number	ASTM D2896	mg KOH/g	8		9.7
HTHS Viscosity	ASTM D4683	mPa.s	2.6	2.9	
NOACK Volatility	ASTM D5800	%		13	
Density	ASTM D792	@ 15°C			0.846

SAFETY PRECAUTIONS

Please see our latest EC Safety Data Sheets for details.

TRANSPORT CLASSIFICATION

Please see our latest EC Safety Data Sheets for details.

