

TECHNICAL DATA

Granville Lithium EPO - Chassis Grease

12.5kg

PRODUCT DESCRIPTION

Granville EPO Grease is a premium quality grease designed for centralised lubrication systems. It is also suitable for anti-friction and plain bearings subjected to high load conditions. EPO Grease can also be used for gearboxes designed to operate with a semifluid slumping grease.

PRODUCT BENEFITS

- * Excellent extreme pressure and anti-wear performance
- * High degree of corrosion protection
- * Highly versatile semi-fluid grease for autolube systems



PART NO

2337

BARCODE

N/A

DIRECTIONS FOR USE

EPO Grease can be applied manually or via a centralised lubricating SIZE system capable of pumping NLGI No. 0 grease.

As with all grease used for the first time, check compatibility with the grease applied previously and, if necessary, purge bearing prior to application. Likewise, as a general rule, take care not to overlubricate and apply only the quantity of grease recommended by the manufacturer.

STORAGE INSTRUCTIONS

Store sealed in a cool, dry place

SHELF LIFE

3 years from date of manufature.

SPECIFICATION INFORMATION

Operating Temperature: -30°C to +110°C Worked penetration: 355 to 385 NLGI Classification: 0

Appearance

: Brown smooth semi-fluid grease



Granville Oil & Chemicals Ltd. 29 Goldthorpe Ind. Est., Goldthorpe, Rotherham, S63 9BL ENGLAND Tel: +44 (0)1709 890099 • www.granvilleoil.com

12.5kg

Revision: 1 | Date: 16/03/2012



TECHNICAL DATA

Granville Lithium EPO – Chassis Grease

12.5kg

Odour Solubility : Characteristic

: Insoluble in water

SAFETY PRECAUTIONS

Please see our latest EC Safety Data Sheets for details.

TRANSPORT CLASSIFICATION

Please see our latest EC Safety Data Sheets for details.



Granville Oil & Chemicals Ltd. 29 Goldthorpe Ind. Est., Goldthorpe, Rotherham, S63 9BL ENGLAND Tel: +44 (0)1709 890099 • www.granvilleoil.com